

1U-G40-2+2xUSB3.0 2-LAN



CPU	: N2830/N2840/N2940/J1900/2980U/3556U/I3-4005U/I5-4260U
RAM	: 1*DDR3 1600Maximum 8GB RAM
Hard Drive	: 1*SATA connector,1*MSATA connector
Video Card	: Intel HD Graphics
Display Connection	: VGA Display connector, 1*HDMI
Front I/O	: 2xINTEL i211 gigabit network card, , 2xUSB3.0, 4*USB2.0, 1*video interface, 2xRS232 com
Expansion Ports	: USB2.0, Mini PCie (PCI, either wifi or 4G)
CPU Fan	: Passive heat dissipation
Power	: External power 12V 6ADC5.5*2.5 (optional)
O/S	: Windows,10,Server2012/EXSI/Ikuai/Mikrotik/Openwrt/Ubuntu/Centos/Pfsense/Lede/Liunx
Humidity	: 0%~60% (Noncondensing state)
Temperature	: 0°C~60°C
Certifications	: CE/CCC/FCC Class A/ROHS
Dimension	: 159*124*34MM(L*W*H)
Machine Fan	: NO FAN
Material	: Aluminum 1*2.5Hard drive position7-9MM height
Packing Contains	: OPS, a power cord, a pair of rack ears, a pack of screws, a set of warranty cards