

1U-G48-4+1USB2.0 4-LAN

....



CPU	: N2830/N2840/J1900/J3160/J3455/J4205
RAM	: 1*DDR3L 1333/1600Maximum 8GB RAM
Hard Drive	: 1*SATA connector,1*MSATA connector
Video Card	: Intel HD Graphics
Display Connection	: 1*HDMI, 1*VGA
Front I/O	: 4*INTEL I211 gigabit network ports, 1*USB2.0, 1*USB3.0
Expansion Ports	: USB2.0, Mini PCie (USB and 4G support)
CPU Fan	: Passive heat dissipation
Power	: External power 12V 4ADC5.5*2.5 interface (optional)
O/S	: Windows,10,Server2012/EXSI/Ikuai/Mikrotik/Openwrt/Ubuntu/Centos/Pfsense/Lede/Liunx
Humidity	: 0%~60% (Noncondensing state)
Temperature	: 0°C~60°C
Certifications	: CE/CCC/FCC Class A/ROHS
Dimension	: 134*126*40mm (L*W*H)
Machine Fan	: NO FAN (OPTIONAL)
Material	: Aluminum 1*2.5Hard drive position7-9MM height
Packing Contains	: OPS, a power cord, a pair of rack ears, a pack of screws, a set of warranty cards