

# 1U-D525-19inch **6-LAN**



CPU	: D525/2980U/3855U/I3-2350M/I3-3110M/ I5-3320M/I7-3520M
RAM	: 1*DDR3 1333Maximum 4GB RAM
Hard Drive	: 1*SATA connector,1*MSATA connector
Video Card	: Intel HD Graphics
Display Connection	: VGA Display connector
Front I/O	: 6*INTE82583V Gbe, 2*USB3.0 (2980U,3855U)/2*USB 2.0 (I3,I5,I7) 1*CONSOLE
Expansion Ports	: USB2.0, Mini PCie (USB support)
CPU Fan	: Silent Fan
Power	: Mingwei power supply, 110V-240V 50-60Hz AC Input (Outta Power 12V 4A)
O/S	: Windows,10,Server2012/EXSI/Ikuai/Mikrotik/Openwrt/Ubuntu/Centos/Pfsense/Lede/Liunx
Humidity	: 0%~60% (Noncondensing state)
Te mperature	: 0°C~60°C
Certifications	: CE/CCC/FCC Class A/ROHS
Dimension	: 440*250*45mmL*W*H(Internal dust protector)
Machine Fan	: 40*40*10mm Double turbo fan
Material	: Cold Tie Steel 1*3.5/2.5Hard driveposition
Packing Contains	: OPS, a power cord, a pair of rack ears, a pack of screws, a set of warranty cards