

1U-G47-6+4xUSB3.0 6-LAN



CPU	: 3855U/3865U/3965U/4405U/4415U/I3-7100U/I5-7200U/I7-7500U
RAM	: 1*DDR4 2133-2666Maximum 32GB RAM
Hard Drive	: 1*SATA connector,1*MSATA connector
Video Card	: Intel HD Graphics
Display Connection	: VGA Display connector
Front I/O	: 6xINTEL i211gigabit network card, 4xUSB3.0, 2*USB2.0, 1xRS232 com
Expansion Ports	: USB2.0, Mini PCie (PCI, either wifi or 4G)
CPU Fan	: Passive heat dissipation
Power	: External power 12V 6ADC5.5*2.5 (optional)
O/S	: Windows,10,Server2012/EXSI/Ikuai/Mikrotik/Openwrt/Ubuntu /Centos/Pfsense/Lede/Liunx
Humidity	: 0%~60% (Noncondensing state)
Te mperature	: 0°C~60°C
Certifications	: CE/CCC/FCC Class A/ROHS
Dimension	: 187*111*50mm(L*W*H)
Machine Fan	: NO FAN
Material	: Aluminum 1*2.5Hard drive position7-9MM height
Packing Contains	: OPS, a power cord, a pair of rack ears, a pack of screws, a set of warranty cards