

2U-B360-MATX 2-LAN



CPU	: INTEL 8/9代115 Celeron G5400/core i3i5i7
RAM	: 2*DDR4Maximum 32GB RAM
Hard Drive	: 4*SATA 3.0 connector,1*M.2 connector
Video Card	: Intel HD Graphics
Display Connection	: 1*HDMI, 1*VGA,1*DP
Front I/O	: 2*intel i211 gigabit network card, PEX supported , 2xUSB3.0, 1*video interface, 1*PCIE3.0x16 PCI, wireless supported, 5*RS232 serial port
Expansion Ports	: USB2.0, 1*PCIE2.0*16 PCI, wireless supported (optional), 1*mini PCIE
CPU Fan	: Silent Fan
Power	: HANGJIA power supply, 110V-240V 50-60Hz AC Input (Outta Power 12V 4A)
O/S	: Windows,10,Server2012/EXSI/Ikuai/Mikrotik/Openwrt/Ubuntu /Centos/Pfsense/Lede/Liunx
Humidity	: 0%~60% (Noncondensing state)
Te mperature	: 0°C~60°C
Certifications	: CE/CCC/FCC Class A/ROHS
Dimension	: 440*430*90mm(L*W*H)
Machine Fan	: NO FAN (OPTIONAL)
Material	: Cold Tie Steel 2*3.5 Hard drive position
Packing Contains	: OPS, a power cord, a pair of rack ears, a pack of screws, a set of warranty cards