

1U-H170-12 NETWORK PORTS **8-LAN**



CPU	: INTEL i3i5i7i9 6/7/8/9th generation1151 CELERON G3900/G4900 /G5400
RAM	: 2*DDR4 2133-2666, maximum64GB RAM
Hard Drive	: 1*2.5 inch SATA connector,1*MSATA connector, 3* SATA3.0, 1*CF slot
Video Card	: Intel HD Graphics
Display Connection	: 1*VGA Display connector, 1*HDMI Display connector
Front I/O	: 8*INTEL I211 Gigabit Network Cards, 2*USB3.0, 1*CONSOLE
Expansion Ports	: Gigabit electrical port: 4*intel82580B
CPU Fan	: Silent Fan
Power	: Meiji power supply, 110V-240V 50-60Hz AC Input (Outta Power 12V 4A)
O/S	: Windows,10,Server2012/EXSI/Ikuai/Mikrotik/Openwrt/Ubuntu /Centos/Pfsense/Lede/Liunx
Humidity	: 0%~60% (Noncondensing state)
Te mperature	: 0°C~60°C
Certifications	: CE/CCC/FCC Class A/ROHS
Dimension	: 440*250*45mmL*W*H(Internal dust protector)
Machine Fan	: 40*40*10mm Double turbo fan
Material	: Cold Tie Steel 1*3.5/2.5Hard drive position
Packing Contains	: OPS, a power cord, a pair of rack ears, a pack of screws, a set of warranty cards