

# 2U-IPC-110 2-LAN



CPU	: INTEL 6/7 1151 celeron G3900/core i3i5i7
RAM	: 2*DDR4Maximum 32GB RAM
Hard Drive	: 1*SATA connector,1*MSATA connector
Video Card	: Intel HD Graphics
Display Connection	: VGA Display connector
Front I/O	: 8xINTE82583V Gbe, 2xUSB2.0, 4*USB3.0, USB3.0,4*RS232串口, 1*video interface, 4*PCIE3.0*16 rabbit, wireless supported
Expansion Ports	: USB2.0, 4*PCIE3.0*16 rabbit, wireless supported (optional), 1*mini PCIE
CPU Fan	: Silent Fan
Power	: HANGJIA power supply, 110V-240V 50-60Hz AC Input (Outta Power 12V 4A)
O/S	: Windows,10,Server2012/EXSI/Ikuai/Mikrotik/Openwrt/Ubuntu /Centos/Pfsense/Lede/Liunx
Humidity	: 0%~60% (Noncondensing state)
Te mperature	: 0°C~60°C
Certifications	: CE/CCC/FCC Class A/ROHS
Dimension	: 440*430*90mm( L*W*H )
Machine Fan	: NO FAN ( OPTIONAL )
Material	: Cold Tie Steel 2*3.5 Hard drive position
Packing Contains	: OPS, a power cord, a pair of rack ears, a pack of screws, a set of warranty cards