

2U-H87-8*LAN + 4*SFP+ 8-LAN

....



CPU	: G3250/I3-4150/I5-4460/I7-4770
RAM	: 2*DDR3L Maximum 16GB RAM
Hard Drive	: 1*SATA connector, 1*MSATA connector
Video Card	: Intel HD Graphics
Display Connection	: VGA Display connector
Front I/O	: 8*INTEL 82583V Gigabit Optical Ports, 2*USB2.0, 1*CONSOLE
Expansion Ports	: USB2.0, Mini PCIe (USB support) Optional expanded ports: Gigabit optical port: 4*intel82580EB 10-Gigabit optical port: 4*intel L1710-BM2
CPU Fan	: Silent Fan
Power	: HANGJIA power supply, 110V-240V 50-60Hz AC Input (Outta Power 12V 4A)
O/S	: Windows, 10, Server 2012/EXSI/Ikuai/Mikrotik/Openwrt/Ubuntu /Centos/Pfsense/Lede/Liunx
Humidity	: 0%~60% (Noncondensing state)
Temperature	: 0°C~60°C
Certifications	: CE/CCC/FCC Class A/ROHS
Dimension	: 440*430*90mm(L*W*H)
Machine Fan	: NO FAN (OPTIONAL)
Material	: Cold Tie Steel 2*3.5 Hard drive position
Packing Contains	: OPS, a power cord, a pair of rack ears, a pack of screws, a set of warranty cards