

1U-G30-2+2USB 3.0 2-LAN



CPU	: N2830/N2840/N2940/J1900/2980U/3556U/I3-4005U/I5-4260U
RAM	: 1*DDR3 1333/1600 or DDR4(J4105) Maximum 8GB RAM
Hard Drive	: 1*SATA connector,1*MSATA connector
Video Card	: Intel HD Graphics
Display Connection	: VGA Display connector, 1*HDMI
Front I/O	: 2*Realtek 8111F Gigabit Network Cards, 2*USB3.0, 2*USB2.0, 1*Video Interface, 2*RS232 Com
Expansion Ports	: USB2.0, Mini PCie (PCI, either wifi or 4G)
CPU Fan	: Passive heat dissipation
Power	: External power 12V 6ADC5.5*2.5 (optional)
O/S	: Windows,10,Server2012/EXSI/Ikuai/Mikrotik/Openwrt/Ubuntu/Centos/Pfsense/Lede/Liunx
Humidity	: 0%~60% (Noncondensing state)
Temperature	: 0°C~60°C
Certifications	: CE/CCC/FCC Class A/ROHS
Dimension	: 137*127*40mm(L*W*H)
Machine Fan	: NO FAN
Material	: Aluminum 1*2.5Hard drive position7-9MM height
Packing Contains	: OPS, a power cord, a pack of screws,a set of warranty cards