

1U-B75-6+2USB2.0 6-LAN



CPU	: G1610/G2620/I3-3220/I5-3470/I7-3770/E3-1230v2
RAM	: 2*DDR3L Maximum 16GB RAM
Hard Drive	: 1*SATA connector, 1*MSATA connector
Video Card	: Intel HD Graphics
Display Connection	: VGA Display connector
Front I/O	: 6*inte82583v Gigabit Network Card , 2*USB2.0, 1*Console
Expansion Ports	: USB2.0, Mini PCie (PCI support) Optional gigabit optical port: 2 * Intel i350 10 Gigabit optical port / 2 * Intel 82599ES 10 Gigabit optical port
CPU Fan	: Silent Fan
Power	: Meiji power supply, 110V-240V 50-60Hz AC Input (Outta Power 12V 4A)
O/S	: Windows, 10, Server 2012/EXSI/Ikuai/Mikrotik/Openwrt/Ubuntu /Centos/Pfsense/Lede/Liunx
Humidity	: 0%~60% (Noncondensing state)
Te mperature	: 0°C~60°C
Certifications	: CE/CCC/FCC Class A/ROHS
Dimension	: 440*250*45mmL*W*H(Internal dust protector)
Machine Fan	: 40*40*10mm Double turbo fan
Material	: Cold Tie Steel 1*3.5/2.5Hard drive position
Packing Contains	: OPS, a power cord, a pair of rack ears, a pack of screws, a set of warranty cards