

G30-01-J1900 4-LAN



CPU	: INTEL celeron J1900 four core four threads 2.0G
RAM	: 1*DDR3L Maximum 8GB RAM
Hard Drive	: 1*SATA connector, 1*MSATA connector
Video Card	: Intel HD Graphics
Display Connection	: VGA Display connector, 1*HDMI
Front I/O	: 4xINTEL I211 gigabit network card, 1xUSB2.0, 1xUSB3.0, SIM card slot
Expansion Ports	: USB2.0, Mini PCie (USB and 4G support)
CPU Fan	: Passive heat dissipation
Power	: External power station up to 12V 4adc5.5 * 2.5 interface (optional)
O/S	: Windows,10,Server2012/EXSI/Ikuai/Mikrotik/Openwrt/Ubuntu/Centos/Pfsense/Lede/Liunx
Humidity	: 0%~60% (Noncondensing state)
Temperature	: 0°C~60°C
Certifications	: CE/CCC/FCC Class A/ROHS
Dimension	: 137*127*40mmmm (L*W*H)
Machine Fan	: NO FAN (OPTIONAL)
Material	: Cold Tie Steel 2*3.5 Hard drive position
Packing Contains	: OPS, a power cord, a pair of rack ears, a pack of screws, a set of warranty cards